



The Smart Choice: High-flow Automatic Pre-Filter



Safe

Healthy

Efficient

www.pentair.com



Self-Cleaning

Built-in digital timer automatically starts the backflushing process at pre-set time.



Clear Filter Housing

Easy monitoring of the water quality by looking at dirt accumulated on strainer.



Large LCD Display

Dual-button interface for easy setting and operation.



Backup Battery Power

Automatically activates when the normal power supply is interrupted.



ABF-10



MBF-10

Technical Specifications:

	ABF-10 Pre-Filter	MBF-10 Pre-Filter
Inlet & Outlet	3/4" NPT thread	3/4" NPT thread
Operating Pressure	15 - 60 psi	15 - 60 psi
Maximum Flow Rate	4 m ³ /h	4 m ³ /h
Maximum Capacity*	15000 m ³	15000 m ³
Control Method	Automatic	Manual
Power Requirement	220V-250V/50-60Hz or 4 AA Batteries	None
Water Temperature	5 ~ 38°C	5 ~ 38°C
Filtration Accuracy	70-90 microns	70-90 microns
Filter Cartridge Lifespan	5 years	5 years

*Blackflushing is required after every 50m³.

Pentair South East Asia Offices

Singapore: 390 Havelock Road, #04-01 King's Centre, Singapore. Tel:+65 6768 5800.

Thailand: 16th Floor, The Ninth Towers, Grand RAMA 9, Tower B, 33/4 Rama 9 Road, Huaykwang, Bangkok 10310, Thailand. Tel:+662 168 1092.

Philippines: 5th Floor MAIA Suites, 1747 Nicanor Garcia Street Corner, D.Oilman Street, Makati City, Philippines. Tel:+632 824 3825.

www.pentair.com