Smart, Suttainable Water Solutions.

Pentair Backflush Prefilter



Pentair Offices in South East Asia

Singapore 390 Havelock Road #04-01 King's Centre Singapore 169662 Tel: +6567685900

Thailand

16th Floor, The Ninth Towers Grand RAMA 9, Tower B 33/4 Rama 9 Road, Huaykwang Bangkok 10310, Thailand Tel: +6621681092

Philippines

5th Floor MAIA Suites 1747 Nicanor Garcia Street corner D.Oliman Street Makati City, Philippines Tel: +632824 3825



Clean Water for the Whole House Pentair Backflush Prefilter



Frontline filtration for Purified Water



Incomplete filtration

SUS 316

20 µm 40 µm 60 µm 80 µm

*Filtered particles refer to pollutants larger than 40 microns.

Blocked filter

High-flow, high-precision pre-filtration

Effectively removes large particles such as dirt and rust to protect terminal water purification equipment.

40 µm precision prefilter provides water that is clean and safe Effective filtration without filter blockage issues.

3 m³/h flow rate ensures enough water for the whole family Satisfies your family's water usage needs.

Grade 316 Stainless Steel Filter

One System with Double the Protection

Wear resistant, corrosion resistant, and rust resistant. Double stainless steel filters for worry-free filtration and cleaning.



steel filter





Backflush rinsing instantly clears away pollutants

Switch water flow instantly for excellent pollutant removal performance

Filtration

Water flows into the system and passes through the filter which stops impurities.

Backflush

When the direction of flow >>

is changed, water flows through the backflush filter and forces impurities caught in the main filter's external wall outwards.

Backflush rinses the lower stainless steel filter from the inside out, effectively dislodging any impurities caught in the filter's surface.



360° Spinning Scraper **Cleans a Second Time**

For a more thorough clean

Spinning scraper cleans a second time after backflushing Transparent filter housing Stubborn pollutants are further scraped away to ensure a thorough clean.



User-friendly Design 3 Durable and Thoughtful

12 Months

Auxiliary monthly recording dial

User-friendly design for convenient recording of rinsing by month

0	
(~~)	
U	

Front-facing precision pressure gauge

Easily monitor water pressure in real time at a glance

-
414
1 TAT /

High-strength transparent filter housing

Provides a clear view of impurities and particulates

6

Rapid backflush design


Simply open the drainage valve to start backflushing, and guickly and conveniently rinse the filter and housing

Product Specifications

Product Model	BB3011-00
Product Dimensions (mm), H x W x D	293x169x88
Micron Rating (µm)	40
Clean water flow rate (m3/h)	3.0

Capacity (m ³)	1000	
Inlet Water Pressure (PSI)	14.5 – 72.5 PSI (1 - 5 bar)	
Operating Temperature* (°C)	5 - 38	

* Do no place the product under direct sunlight or outdoor (Health permit no. line deleted)



Flow of

wator

Backflush filter

Main filter



*Filtered particles refer to pollutants larger than 40 microns.