



PNR Salt Chlorinator

New Pentair Salt Chlorinator with separated cell and controller for a safe, effective and easy pool sanitation

PNR-ECO SERIES



Salt Water Chlorinator with productions from 10g/h to 35g/h for residential applications

-Optional: water flow sensor

Features:

- Manual regulation of chlorine
- Automatic indicators of low salt and excess salt
- Cleaning cycles can be changed
- Able to work with seawater, up to 35000ppm
- Switch mode power supply. Low energy consumption

Automatic alarms

- Caused by low water flow
- Caused by gas accumulation in the cell
- Caused by overload
- Caused by short circuit
- Caused by high temperature
- Caused by low salt levels

PNR-ECO-10	PNR-ECO-15	PNR-ECO-20	PNR-ECO-25	PNR-ECO-35	
230Vac - 50Hz / 60Hz					Power supply
10gr/h	15gr/h	20gr/h	25gr/h	35gr/h	Gr/hour production
75W	112.5W	150W	187.5W	263W	Max power
250 x 308 x 89 mm					Machine dimensions
460 x 430 x 220 mm					Packaging dimensions
6kg					Machine weight





PNR-CHLOR SERIES



Salt water chlorinator with productions from 10g/h to 35g/h for residential pools

Optional: pH probe, ORP probe, Temperature probe, Chlorine probe and water flow sensor

Features:

- Manual and automatic regulation of chlorine
- Indicators of ORP and pH values with the optional kits
- Automatic indicators of low salt and excess salt
- Cleaning cycles can be changed
- Able to work with seawater, up to 35000ppm
- Switch mode power supply. Low energy consumption

Automatic alarms

- Caused by low water flow
- Caused by gas accumulation in the cell
- Caused by overload
- Caused by short circuit
- Caused by high temperature
- Caused by low salt levels

PNR-CHLOR-10	PNR-CHLOR-15	PNR-CHLOR-20	PNR-CHLOR-25	PNR-CHLOR-35	
230Vac - 50Hz / 60Hz					Power supply
10gr/h	15gr/h	20gr/h	25gr/h	35gr/h	Gr/hour production
75W	112.5W	150W	187.5W	263W	Max power
250 x 308 x 89 mm					Machine dimensions
460 x 430 x 220 mm					Packaging dimensions
6 kg					Machine weight





PNR-COM SERIES



Salt water chlorinator with productions from 50g/h to 200g/h. For semi-commercial and commercial pools.

Optional: pH probe, ORP probe, free chlorine probe, temperature probe and water flow sensor

Features:

- Manual and automatic regulation of chlorine
- Indicators of ORP and pH values with the optional kits
- Automatic indicators of low salt and excess salt
- Cleaning cycles can be changed
- Able to work with seawater, up to 35000ppm
- Switch mode power supply. Low energy consumption

Automatic alarms

- Caused by low water flow
- Caused by overload
- Caused by short circuit
- Caused by high temperature
- Caused by low salt levels

PNR-COM-50	PNR-COM-70	PNR-COM-100	PNR-COM-150	PNR-COM-200	
230Vac - 50Hz / 60Hz					Power supply
50gr/h	70gr/h	100gr/h	150gr/h	200gr/h	Gr/hour Production
275W	385W	550W	825W	932W	Max power
250x308x89 mm				250x308x260mm	Machine dimensions
6Kg					Machine weight
400x430x220mm		460x430x440mm		570x390x270mm (controller only)	Packaging dimensions



China | Singapore | Thailand | pentair.com

Win Win Engineering Supply Co.,Ltd. (Head Office)
7/11 Alley 01 Kanchanaphisek 5/5, Kanchanaphisek Rd,
Tha-reang, Bang Khen, Bangkok 10220

+662-989-1111

+662-130-6134-35

Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer. P1-108 10/18 ©2020 Pentair Water Pool and Spa, Inc., All rights reserved.