

Everpure 6TPro Replacement Cartridge

Applicable for commercial water purifier MRSGo-400S



Type selection

SA21083: Everpure 6TPro Replacement Cartridge

Features & Benefits

- 0.5 micron¹ filtration accuracy ¹
- Dirt-holding capabilities ²
- Chlorine, carbon tetrachloride, volatile phenol and other organics reduction for commercial application ²
- Silver loaded formula ¹

Installation tips

- Install vertically with cartridge hanging down.
- Allow 64mm clearance below the cartridge for easy cartridge replacement.
- Flush cartridge by running water through filter for thirty (30) minutes at full flow.

Operation tips

- Change cartridges on a regular 6-12 month preventative maintenance program.
- The service life is the recommended replacement cycle. The actual service life of the cartridge will vary depending on the actual water usage conditions and local tap water quality
- Change cartridges when capacity is reached or when pressure falls below 10 psi (0.7 bar).
- Always flush the filter cartridge at time of installation and cartridge change

Sizing

- Service flow rate³: 2.5Gpm (9.5Lpm)
- **Rated capacity³**: 8,000Gallons (30,283L)

¹ In accordance with the water-related product hygiene license approval for adaption system, (Jiangsu) Hygiene-Water (2023) No. 3200-0013

² In accordance with MOH Overall Performance Test Report of cartridge adaptation system MRSGo-400S, report No.: (Environmental Water) Test Report No. 20221187, (Environmental Water) Test Report No. 20221188

³ The treatment capacity refers to the overall performance of the cartridge adaptation system, and is based on the Test Report No. SZ-LAB-2023138003 (G) from the laboratory of Pentair

Everpure 6TPro Replacement Cartridge



Specifications

- Service flow rate ³: 2.5GPM (9.5Lpm)
- Rated capacity ³: 8,000Gallons (30,283L)
- Pressure requirements: 20 - 50 psi (1.4 – 3.5 bar)
- Temperature: 41 - 100°F (5 - 38°C)
- Overall dimensions: $\Phi 8 \times 43.4\text{cm}$

Precautions

- The Everpure integrated cartridge is mainly used for filtering and purifying municipal tap water. It shall not be used to treat water sources not fully disinfected and containing unsafe or unknown microbial loads.
- It is recommended to flush before use after a water cut-off of 48 hours.



Pentair Offices in South East Asia

Singapore

390 Havelock Road
#04-01 King's Centre
Singapore 169662
Tel: +6567685900

Thailand

16th Floor, The Ninth Towers
Grand RAMA 9, Tower B
33/4 Rama 9 Road, Huaykwang
Bangkok 10310, Thailand
Tel: +6621681092

Philippines

5th Floor MAIA Suites
1747 Nicanor Garcia Street corner
D.Oliman Street Makati City, Philippines
Tel: +632824 3825