



# Everpure 6TS Replacement Cartridge

Applicable for commercial water purifier MRSGo-400S



## Type selection

SA21079: Everpure 6TS Replacement Cartridge

## Features & Benefits

- 0.5 micron1 filtration accuracy <sup>1</sup>
- **Dirt-holding capabilities** <sup>2</sup>
- Chlorine, carbon tetrachloride, volatile phenol and other organics reduction for commercial application <sup>2</sup>
- Anti-scaling formula <sup>1</sup>

## Installation tips

- Install vertically with cartridge hanging down.
- Allow 64mm clearance below the cartridge for easy cartridge replacement.
- Flush cartridge by running water through filter for thirty (30) minutes at full flow.

## Operation tips

- Change cartridges on a regular 6-12 month preventative maintenance program.
- The service life is the recommended replacement cycle. The actual service life of the cartridge will vary depending on the actual water usage conditions and local tap water quality
- Change cartridges when capacity is reached or when pressure falls below 10 psi (0.7 bar).
- Always flush the filter cartridge at time of installation and cartridge change

## Sizing

- Service flow rate <sup>3</sup>: 2.5Gpm (9.5Lpm)
- Rated capacity <sup>3</sup>: 35,000Gallons (132,489L)

<sup>1</sup> In accordance with the water-related product hygiene license approval for adaption system, (Jiangsu) Hygiene-Water (2023) No. 3200-0013

<sup>2</sup> In accordance with MOH Overall Performance Test Report of cartridge adaptation system MRSGo-400S, report No.: (Environmental Water) Test Report No. 20221187, (Environmental Water) Test Report No. 20221188

<sup>3</sup> The treatment capacity refers to the overall performance of the cartridge adaptation system, and is based on Test Report SZ-LAB-2023138001 (G) from the laboratory of Pentair

# Everpure 6TS Replacement Cartridge

---



## Specifications

---

- Service flow rate <sup>3</sup>: 2.5GPM (9.5Lpm)
- Rated capacity <sup>3</sup>: 35,000Gallons(132,489L)
- Pressure requirements: 20 - 50 psi (1.4 – 3.5 bar)
- Temperature: 41 - 100°F (5 - 38°C)
- Overall dimensions:  $\Phi 8 \times 43.4\text{cm}$

## Precautions

---

- The Everpure integrated cartridge is mainly used for filtering and purifying municipal tap water. It shall not be used to treat water sources not fully disinfected and containing unsafe or unknown microbial loads.
- It is recommended to flush before use after a water cut-off of 48 hours.



### Pentair Offices in South East Asia

#### Singapore

390 Havelock Road  
#04-01 King's Centre  
Singapore 169662  
Tel: +6567685900

#### Thailand

16th Floor, The Ninth Towers  
Grand RAMA 9, Tower B  
33/4 Rama 9 Road, Huaykwang  
Bangkok 10310, Thailand  
Tel: +6621681092

#### Philippines

5th Floor MAIA Suites  
1747 Nicanor Garcia Street corner  
D.Oliman Street Makati City, Philippines  
Tel: +632824 3825