



7FT-S FILTER CARTRIDGE

High Performance Filter Cartridge for Everpure FT Series



APPLICATIONS

Ice machines, steam and combi ovens, coffee, bubble tea, and restaurants

FEATURES • BENEFITS

- Uses anti-scaling materials which are internationally certified by WQA. No additives. Green and environmentally friendly
- Effectively removes chlorine taste and odour in water to enhance the taste of beverages
- Contains silver-loaded antibacterial formula with 0.5 micron filtration efficiency
- Quick-connect aluminum canister makes filter replacement quick and easy
- Compatible with Everpure water filtration system

7FT-S Replacement Cartridge

INSTALLATION TIPS

- Install vertically so cartridge hangs down
- Allow at least 200mm clearance below the cartridge for easy cartridge replacement and system maintenance
- Resume inlet water supply and flush the whole filtration system for at least 30 minutes after a filter cartridge is installed or replaced

OPERATION TIPS


- Recommended service life of the cartridge: 6 - 12 months
- The service life is a recommended replacement cycle, and the actual lifespan of a cartridge may vary in accordance with the actual water consumption and local tap water quality
- Change a cartridge when its capacity is reached or whenpressure falls below 10psi (0.7bar)
- Always flush the filter cartridge at time of installation and cartridge change

SIZING

- Flow rate¹: 2.5 gpm (9.5 Lpm)
 Rated capacity¹:
- 30,000 gallons (113,562 L)

7FT-S FILTER CARTRIDGE SPECIFICATION SHEET ¹Tested in Pentair laboratory according to NSF-42 standard and verified by third party laboratory.

7FT-S FILTER CARTRIDGE SA21127 (1PK)



SPECIFICATIONS Cartridge

Overall Dimensions Length: 20.65" (53.2 cm) Diameter: 3.15" (8.0 cm)

Working Pressure 0.14 – 0.35MPa, non-shock

Temperature 39 – 104°F (4 – 40°C)

Filter Media Type Activated Carbon Fiber

Performance

Flow Rate¹ 2.5 gpm (9.5 Lpm)

Rated Capacity¹ 20,000 gallons (113,562 L)

NOTE

- Do not use with microbiologically unsafe or of unknown quality water without adequate disinfection before or after the filtration system/ cartridge.
- After stopping the filtration for 48 hours, it is recommended to flush for 10 mins before use.



Pentair Offices in South East Asia

Singapore

390 Havelock Road #04-01 King's Centre Singapore 169662 Tel: +6567685900 Thailand 16th Floor, The Ninth Towers Grand RAMA 9, Tower B 33/4 Rama 9 Road, Huaykwang Bangkok 10310, Thailand Tel: +6621681092

sea.enews@pentair.com | pentair.asia

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. ©2024 Pentair. All Rights Reserved.