



ULTRATEMP VXi HEAT PUMPS




COMMERCIAL RANGE

FEATURES HIGHLIGHTS

- Full Inverter Technology: inverter compressor and variable speed fan
- Soft Start with maximum stability and low energy consumption
- Lower operating noise compared to traditional heat pumps
- Top Fan heat pump with operating air temperature: -15°C to 43/55°C.



ULTRATEMP VXi HEAT PUMPS

Models		UTHP-65-VXi	UTHP-130-VXi	UTHP-250-VXi
Heating Capacity (Air 27°C / Water 26°C / Humid. 80%)				
Heating Capacity	kW	12.20~65.00	28.20~130.00	61.3~250.00
Input Power	kW	0.76~10.65	1.76~20.97	3.81~40.85
COP		6.10~16.10	6.20~16.00	6.12~16.10
Power Boost Mode	kW	80	175	300
Cooling Capacity (Air 43°C / Water 26°C / Humid. 70%)				
Cooling Capacity	kW	8.20~18.40	59.40~73.40	58.30~110.00
Consumed Power	kW	2.02~6.28	13.81~13.85	14.05~35.48
EER		2.93~4.06	4.30~5.30	3.10~4.15
Technical Specifications				
Sound Pressure 1m	dB(A)	60	63	65
Power Supply		380 / 3Ph / 50Hz & 60 Hz		
Net Dimensions L/W/H	mm	1750 x 840 x 1750	2170 x 1150 x 2130	2480 x 1330 x 2360
Operating Air Temperature	°C	-15~55		-15~43
Refrigerant		R410 a		
Air Discharge		Vertical		
Certification		CE		
Casing		Galvanized Metal Cabinet		
Connected App and Display	Display	App	Cabinet	
				



Singapore | Philippines | Thailand | pentair.com

• 390 Havelock Road, #04-01 King's Center, Singapore 169662

• 5th Floor Maia Suites, 1747 Nicanor Garcia St. corner D. Oliman St., Makati City, Philippines

• 33/4 The Ninth Towers Grand RAMA 9 (Tower B) 16th Floor, Rama 9 Road, Huaykwang, Bangkok, Thailand 10310

+65 6768 5800

+632-824-3825

+662 1681092

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.

©2023 Pentair. All Rights Reserved.